

Z6

LED Video Controller

Specification V2.2



Overview

Z6 is a professional LED display controller. As video splicer, processor and LED controller in one combined, Z6 has 4K video input capability, UHD and HDR images processing and transmission. Z6 can be applied to high-end rental display and high-resolution LED display perfectly.

Features

Input

- Two 4K inputs: 1×HDMI2.0, 1×DP1.2.
- Six 2K inputs: 4×DVI2×SDI.
- Up to 3840×2160@60Hz resolution.
- 8/10bit color depth.
- HDCP.

Output

- Loading capacity: 8.30 million pixels, maximum width: 8192 pixels, or maximum height: 4096 pixels.
- 16 Neutrik Gigabit Ethernet outputs.
- Ethernet port redundancy and controller redundancy.

Video processing

- HDR display: HDR10 standard.
- Low latency.
- Cropping, scaling and splicing of input images.
- Up to 3 windows, which are freely assignable and can be scaled up and down.
- Brightness adjustment, color temperature adjustment.
- Better gray at low brightness.

Control

- USB port for control or cascading.
- RS232 protocol.
- Control via TCP/UDP protocol and Art-Net protocol in local area network.

Hardware

Front panel




Item	Function
3.5-inch LCD	Display operation menu or system information
Knob	<ul style="list-style-type: none"> Press the knob to enter the submenu or confirm the selection Rotate the knob to select a menu item or adjust parameters
Function shortcut	OK: Enter key ESC: Exit the current menu Bright: Adjust brightness Black: Blackout Lock: Lock keys
Signal selection	PIP: Turn on or off PIP Freeze: Freeze the image HDMI/DP/DVI/SDI1/SDI2: Switch to the video signal

Rear panel



Input	
SDI1,2	2×3G SDI
HDMI	1×HDMI 2.0, 1×HDMI2.0 LOOP, EIA/CEA-861 standard, HDMI2.0 specification, HDCP2.2 compliant
DP	1×DP1.2, DP1.2 specification, HDCP1.3 compliant
DVI1-4	4×DVI, VESA standard, HDCP1.4 compliant
Output	
Port1-16	16×Neutrik Gigabit Ethernet ports
Control	
LAN	Fast Ethernet port, connect to the PC or access the local area network, or as Art-Net control port
USB IN	USB input, connect to the PC for debugging
USB OUT	USB output, as cascading output
Genlock	Input synchronized signal
Genlock Loop	Output synchronized signal
RS232	RJ11(6P6C) port*, connect to the third-party device
Power supply	
MAINS INPUT	AC 100~240V, 50/60Hz, built-in fuse

* DB9 female to RJ11(6P6C) cable:



Signal format

HDMI2.0 (A)			
Standard	EIA/CEA-861 standard, HDMI2.0 specification, HDCP2.2 compliant		
Input	Format		Maximum input resolution
	8bit	RGB444	4096×2160@60Hz
		YCbCr444	
		YCbCr422	
		YCbCr420	
	10bit	RGB444	1920×1080@60Hz
YCbCr444		4096×2160@60Hz	
YCbCr422			
YCbCr420			
Frame rate	23.98,24,25,29.97,30,50,59.94,60		
DP1.2			
Standard	DP1.2 specification, HDCP1.3 compliant		
Input	Format		Maximum input resolution
	8bit	RGB444	4096×2160@60Hz
		YCbCr444	
		YCbCr422	
		YCbCr420	
Frame rate	23.98,24,25,29.97,30,50,59.94,60		
DVI			
Standard	VESA standard, HDCP1.4 compliant		
Input	Format		Maximum input resolution
	8bit	RGB444	1920×1200@60Hz
		YCbCr444	
		YCbCr422	
		YCbCr420	
Frame rate	23.98,24,25,29.97,30,50,59.94,60		
SDI			
Standard	SMPTE-424M/SMPTE-372M/SMPTE-292M standard, 3G-SDI/HD-SDI/SD-SDI		
Input	1080P, 1080i, 720P, support Level A, Level B		
Frame rate	23.98,24,25,29.97,30,50,59.94,60		


Function description

Function	Description
Multi-window display	<ul style="list-style-type: none"> Up to 3 windows. Support window overlay. Minimum size of the window is 64×64 pixels, and maximum 8.30 million pixels. Window size and position can be freely adjusted in the control area of the device.
Cropping	<ul style="list-style-type: none"> All input signals support cropping, and each channel of signals can be cropped once. The size and position of cropping frame can be freely adjusted within the resolution of the video source, and its minimum size is 64×64 pixels.
HDR display	<ul style="list-style-type: none"> HDMI2.0 supports HDR display with HDR10 standard, and supports color space selection. DP/DVI/SDI does not support HDR display.
Low latency	<ul style="list-style-type: none"> Progressive scanning signals support low latency, while interlaced scanning signals do not support low latency.

Parameters

Dimensions (W×H×D)	
Unboxed	482.6mm (19") × 88.0mm (3.5") × 372.6mm (14.7")
Weight	
Net weight	9kg (19.84lbs)
Electrical	
Input voltage	AC100-240V, 50/60Hz
Rated power	70W
Operating environment	
Temperature	-20°C~60°C (-4°F~158°F)
Humidity	0%RH~80%RH, non-condensing
Storage environment	
Temperature	-30°C~80°C (-22°F~176°F)
Humidity	0%RH~90%RH, non-condensing
Certification	
CCC, CE, FCC, IC, CB, cTUVus, EAC, ROHS.	
* If the product does not have the relevant certifications required by the countries or regions where it is to be sold, please contact Colorlight to confirm or address the problem. Otherwise, the customer shall be responsible for the legal risks caused or Colorlight has the right to claim compensation.	

Reference dimensions



Statement

Copyright © 2022 Colorlight Cloud Tech Ltd. . All rights reserved.

Without the express written permission of Colorlight Cloud Tech Ltd., no unit or individual may copy, copy, transcribe or translate part or all of the contents of this book. Not to be used for any commercial or profit-making purposes in any form or by any means.

 Colorlight® The logo is a registered trademark of Colorlight Cloud Tech Ltd.

Without the written permission of the company or the trademark owner, no unit or individual may in any way or for any reason use, reproduce, modify, disseminate, transcribe or infringe all or any part of the above-mentioned trademark, nor may it be bundled with other products. Use sales.

As factors such as product batches and production processes may change, in order to provide accurate product information, specification parameters, and product characteristics in order to match the actual product, the text description and picture effects in the document will be adjusted and revised appropriately. If it is necessary to carry out the above modification and adjustment without prior notice, please refer to the actual product.

Welcome to choose to use the products of Colorlight Cloud Tech Ltd. If you have any questions or suggestions in use, please contact us through official channels, we will try our best to support and listen to your valuable suggestions. For more information and updates, please visit the official website www.colorlightinside.com or scan the QR code.

Service Phone

4008 770 775

Colorlight Cloud Tech Ltd.

Official Website: www.colorlightinside.com
Head Office Address: Room 37F-39F, Building 8, Zone A,
Shenzhen International Innovation Valley, Vanke Cloud City, Dashi Yilu,
Nanshan District, Shenzhen, China

